

Accelerate CSS 5W-40

High Performance Low Friction Motor Oil for Passenger Cars

Product Description

ACCELERATE CSS 5W-40 is a low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic components and mineral base stocks and additives of most progressive technology.

ACCELERATE CSS 5W-40 is suitable under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged. By its optimized formulation provides lowered fuel- and oil consumption. Because of its extended viscosity range the all seasons use is possible.

The dispersing power, expressed by the performance level of this product, prevents deposits and pluggings in the oil circuit and thus keeps the engine clean. Modern oxidation inhibitors extend the service life of the oil and the optimal wear protection cares for long engine life.

Specification

API SL / CF

Typical Properties

.Specification variations in these characteristics may occur.

	unit	Value	method
Density at 15°C	kg/m ³	853	DIN 51 757
Kin. viscosity at 40°C	mm ² /s	83,4	DIN 51 562
Kin. viscosity at 100°C	mm ² /s	13,9	DIN 51 562
Viscosity index		172	DIN ISO 2909
Dyn. viscosity at -30°C	mPa.s	6160	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flash point	°C	220	DIN ISO 2592
TBN	mg KOH/g	8,5	DIN ISO 3771