



## Accelerate CSX 10W-30

### High Performance Low Friction Motor Oil for Passenger Cars

#### Product Description

ACCELERATE CSX 10W30 is a high performance low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic oils and mineral base stocks and additives of most progressive technology.

Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged, and for vans , too.

ACCELERATE CSX 10W30 by its optimized formulation provides lowered fuel and oil consumption. Because of its extended viscosity range the all seasons use is possible. A special booster raises the quality level up to API SN, which provides improved oxidation resistance, improved deposit protection, better wear protection, and better low-temperature performance over the life of the oil. This leads to an improved motor cleanliness and at least to an extended motor life.

#### Specification

**ACEA A3- / B4-12**

**API SN / CF**

**VW 505 00**

**MB 229.1**

#### Typical Properties

.Specification variations in these characteristics may occur.

	unit	Value	method
Density at 15°C	kg/m <sup>3</sup>	865	DIN 51 757
Kin. viscosity at 40°C	mm <sup>2</sup> /s	66,9	DIN 51 562
Kin. viscosity at 100°C	mm <sup>2</sup> /s	10,7	DIN 51 562
Viscosity index		149	DIN ISO 2909
Dyn. viscosity at -25°C	mPa.s	6360	DIN 51 377
Pourpoint	°C	-36	DIN ISO 3016
Flash point	°C	220	DIN ISO 2592
TBN	mg KOH/g	10,2	DIN ISO 3771

Tribu-Fluid GmbH • Benzstrasse 22 • D-41515 Grevenbroich  
Email : info@tribu-fluid.de