

Accelerate Diesel HMB 20W-50

High Performance Multigrade Motor Oil

Product Description

ACCELERATE Diesel HMB 20W50 is a high performance motor oil for modern heavily stressed diesel engines inclusive turbo charger. Because of its outstanding additive technology it also comes up to the most severe requirements of gasoline engines. This makes it being excellent provider for mixed-fleet whenever the viscosity-level 20W50 is indicated or required because of the climatical conditions.

ACCELERATE Diesel HMB 20W50 has an excellent thermal/oxidative stability which reduces sludge built-up and deposits. Highest TBN-reserve allows maximum oil drain intervals. Another advantages are minimization efficiently bore polishing, reducing oil aging, even at high temperatures and best seal and elastomer compatibility.

ACCELERATE Diesel HMB 20W50 is especially recommended for fleets operating in severe on and off-highway service applications as an all-season oil in warm and tropical climate.

Specification

ACEA A3- / B4-04 ACEA E7-04

API CI-4 / SL

MB 228.3 & 229.1

MTU Typ 2

MAN M 3275

Typical Properties

Specification variations in these characteristics may occur.

	unit	Value	method
Density at 15°C	kg/m ³	880	DIN 51 757
Kin. viscosity at 40°C	mm ² /s	137,3	DIN 51 562
Kin. viscosity at 100°C	mm ² /s	17,7	DIN 51 562
Viscosity index		142	DIN ISO 2909
Dyn. viscosity at -15°C	mPa.s	7750	DIN 51 377
Pourpoint	°C	-33	DIN ISO 3016
Flash point	°C	218	DIN ISO 2592
TBN	mg KOH/g	10,6	DIN ISO 3771