



Accelerate Diesel HSS 10W-40

High Performance Low Friction Oil

Product Description

ACCELERATE Diesel HSS 10W40 is produced from mineral base oils and hydro-cracked products. Combined with a special additive package it has become a quality product, which satisfies the requirements of the modern engine generation of diesel motors and gasoline motors as well.

ACCELERATE Diesel HSS 10W40 provide trouble-free operation even under extreme operating conditions. Reducing early oil aging even at high temperatures because of high oxidation stability and assures a long engine-life caused by outstanding wear protection. It allows maximal oil drain intervals, like specified by the manufacturer

ACCELERATE Diesel HSS 10W40 is especially applicable for engines, which because of the advanced construction, as turbocharger or poor-mix operation, make very special demands on the lubricant.

Specification

ACEA A3- / B4-04 ACEA E7-04
API CI-4 / SL
Volvo VDS-3
MAN M 3275
MB 228.3

MTU Type 2
DEUTZ DQC III-05
Mack EO-M Plus
Caterpillar ECF-1a
Cummins CES 20076 / 20077

Typical Properties

Specification variations in these characteristics may occur.

	unit	Value	method
Density at 15°C	kg/m ³	867	DIN 51 757
Kin. viscosity at 40°C	mm ² /s	97,4	DIN 51 562
Kin. viscosity at 100°C	mm ² /s	14,5	DIN 51 562
Viscosity index		155	DIN ISO 2909
Dyn. viscosity at -25°C	mPa.s	6380	DIN 51 377
Pourpoint	°C	-33	DIN ISO 3016
Flash point	°C	212	DIN ISO 2592
TBN	mg KOH/g	10,5	DIN ISO 3771