

Accelerate High Power CSS 10W-30

High Performance Low Friction Motor Oil for Passenger Cars

Product Description

ACCELERATE High power CCS10W30 is a low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic components and mineral base stocks and additives of most progressive technology.

ACCELERATE High Power CCS 10W30 is suitable under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged. By its optimized formulation provides lowered fuel- and oil consumption. Because of its extended viscosity range the all seasons use is possible.

The dispersing power, expressed by the performance level of this product, prevents deposits and pluggings in the oil circuit and thus keeps the engine clean. Modern oxidation inhibitors extend the service life of the oil and the optimal wear protection cares for long engine life.

Specification

ACEA A3- / B4-04

API SL / CF

VW 505 00

MB 229.1

Typical Properties

.Specification variations in these characteristics may occur.

	unit	Value	method
Density at 15°C	kg/m ³	869	DIN 51 757
Kin. viscosity at 40°C	mm ² /s	75,1	DIN 51 562
Kin. viscosity at 100°C	mm ² /s	11,2	DIN 51 562
Viscosity index		140	DIN ISO 2909
Dyn. viscosity at -25°C	mPa.s	6450	DIN 51 377
Pourpoint	°C	-36	DIN ISO 3016
Flash point	°C	222	DIN ISO 2592
TBN	mg KOH/g	8,5	DIN ISO 3771