



Accelerate High Power CSS 15W-40

High Performance Multigrade Motor Oil for Passenger Cars

Product Description

ACCELERATE high Power CCS 15W40 is a multigrade motor oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic components and mineral base stocks and additives of most progressive technology.

ACCELERATE high Power CCS 15W40 is suitable under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged. By its optimized formulation provides lowered fuel- and oil consumption. Because of its extended viscosity range the all seasons use is possible.

The dispersing power, expressed by the performance level of this product, prevents deposits and pluggings in the oil circuit and thus keeps the engine clean. Modern oxidation inhibitors extend the service life of the oil and the optimal wear protection cares for long engine life.

Specification

ACEA A3- / B4-04

API SL / CF

VW 505 00

MB 229.1

Typical Properties

Specification variations in these characteristics may occur.

	unit	Value	method
Density at 15°C	kg/m ³	868	DIN 51 757
Kin. viscosity at 40°C	mm ² /s	95	DIN 51 562
Kin. viscosity at 100°C	mm ² /s	14,5	DIN 51 562
Viscosity index		158	DIN ISO 2909
Dyn. viscosity at -20°C	mPa.s	6780	DIN 51 377
Pourpoint	°C	-33	DIN ISO 3016
Flash point	°C	210	DIN ISO 2592
TBN	mg KOH/g	8,5	DIN ISO 3771