



## Accelerate High Power CSX 5W-30

---

### Fully Synthetic High Performance Low Friction Oil for Passenger Car Engines

#### Product Description

ACCELERATE High power CSX 5W-30 is a fully synthetic low friction oil for all passenger car gasoline- and diesel-engines. It is exclusively made from high quality synthese baseoil, which are combined with additives of the most progressive technology.

ACCELERATE High power CSX 5W-30 provides reduced oil- and fuel-consumption because of its optimized formulation. Excellent dispersancy prevents deposits und pluggings in the oil circuit and thus keeps the motor clean. Outstanding low-temperature properties enable smooth cold start and quick oiling of the engine, even at frost. Modern oxidation inhibitors and the fully synthetic base increase the service life of the oil and the assured wear protection are best conditions for a long motor life.

#### Specification

**ACEA A3- / B4-08**

**API SN / CF**

#### Typical Properties

.Specification variations in these characteristics may occur.

|                         | unit               | Value | method       |
|-------------------------|--------------------|-------|--------------|
| Density at 15°C         | kg/m <sup>3</sup>  | 855   | DIN 51 757   |
| Kin. viscosity at 40°C  | mm <sup>2</sup> /s | 62    | DIN 51 562   |
| Kin. viscosity at 100°C | mm <sup>2</sup> /s | 10,6  | DIN 51 562   |
| Viscosity index         |                    | 163   | DIN ISO 2909 |
| Dyn. viscosity at -30°C | mPa.s              | 5230  | DIN 51 377   |
| Pourpoint               | °C                 | -42   | DIN ISO 3016 |
| Flash point             | °C                 | 230   | DIN ISO 2592 |
| TBN                     | mg KOH/g           | 8,1   | DIN ISO 3771 |

Tribu-Fluid GmbH • Benzstrasse 22 • D-41515 Grevenbroich  
Email : info@tribu-fluid.de