



Accelerate High Power GF5 5W-20

Fully Synthetic Fuel Efficient Engine Oil

Product Description

ACCELERATE High power GF5 5W20 is a high performance lubricant, which especially is designed for the most advanced gasoline and diesel engines of passenger cars, which are operated with low viscosity fuel saving engine oils. It is suitable for use in all types of modern vehicles where this viscosity grade is recommended. This includes high-performance turbo-charged, supercharged gasoline multi-valve fuel injected engines found in passenger cars and light vans.

ACCELERATE High power GF5 5W20 is designed on base of synthetic oils only. It persuades by an excellent lubricity and shows outstanding properties and benefits :

- stable lubrication film at all operation conditions.
- outstanding cold starting properties even at low temperatures
- long motor life by complex wear protection and cleanliness from cylinder head down to oil sump.
- low oil consumption and high fuel efficiency.
- lower environmental impact by reduced exhaust gas emissions and long oil drain intervals

Specification

API SN

ILSAC GF-5

Dexos 1

Typical Properties

.Specification variations in these characteristics may occur.

	unit	Value	method
Density at 15°C	kg/m ³	852	DIN 51 757
Kin. viscosity at 40°C	mm ² /s	47,5	DIN 51 562
Kin. viscosity at 100°C	mm ² /s	8,5	DIN 51 562
Viscosity index		157	DIN ISO 2909
Dyn. viscosity at -30°C	mPa.s	4750	DIN 51 377
Pourpoint	°C	-45	DIN ISO 3016
Flash point	°C	208	DIN ISO 2592
TBN	mg KOH/g	7,9	DIN ISO 3771