

Accelerate ATF DX II D

Description/Application/Properties

Accelerate ATF DX II D is a highly developed gear oil, which meets the requirements of the most modern automatic gears of passenger and commercial cars, other vehicles and aggregates.

Accelerate ATF DX II D is an Automatic Transmission Fluid to be universally used in all automatic transmissions, power steering and hydraulics, the manufacturer of which have recommended an ATF according to GM-specification DEXRON® II.

Accelerate ATF DX II D meets the strongest requirements of gear- and machine manufacturers and due to its high quality level it provides optimal operating reliability and endurance of all aggregates to be lubricated.

- excellent lubrication of highly stressed torque converters and load change gears
- very good low- and high-temperature properties
- optimal balanced frictional behavior for short gear change intervals
- very good shear stability, low foaming tendency and long operating expectations

Specification/Recommendation

- GM DEXRON® II D
- ZF TE-ML 03D, 04D, 09A, 11A, 14A
- Allison C3/C4
- Voith
- MAN 339, Type D
- Ford SQM-9010B ; Ford M2C-138CJ, 166H, 185A
- MB 236.7
- Caterpillar TO-2

Accelerate ATF DX II D	unit	value	method
Density at 15°C	kg/m ³	851	DIN 51 757
Viscosity at 40°C	mm ² /s	37	DIN 51 562
Viscosity at 100°C	mm ² /s	7,9	DIN 51 562
Viscosity index		195	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash point COC	°C	218	DIN ISO 2592